



Part Number: 9928

Hook- Up/ Lead Wire UL AWM Style 1007 & 1569, (1) 28 AWG (7x36) TC, PVC, 300V 80°C, 300V 105°C

[🛒 Request Sample](#)

Product Description

One 28 AWG stranded (7x36) tinned copper conductor, PVC insulation.

Technical Specifications

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material | No. of Conductors |
|-----|-----------|--------------------|-------------------|
| 28 | 7x36 | TC - Tinned Copper | 1 |

| | |
|------------------|--------|
| Conductor Count: | 1 |
| Conductor Size: | 28 AWG |

Insulation

| Material | Nominal Diameter | Nominal Wall Thickness | Min. Average Wall Thickness |
|--------------------------|------------------|------------------------|-----------------------------|
| PVC - Polyvinyl Chloride | 0.047 in | 0.016 in | 0.015 in |

Outer Jacket Material

| |
|-----------------|
| Material |
| No Jacket |

Electrical Characteristics

| | |
|------------|------------|
| Shielding: | Unshielded |
|------------|------------|

Voltage

| Non-UL Voltage Rating | UL Voltage Rating |
|-----------------------|-------------------|
| 300 V | 300 V |

Temperature Range

| | |
|---------------------|-------|
| Non-UL Temp Rating: | 105°C |
| UL Temp Rating: | 105°C |

Mechanical Characteristics

| | |
|--------------------|----------------|
| Bulk Cable Weight: | 1.5 lbs/1000ft |
|--------------------|----------------|

Standards

| | |
|-------------------------|---|
| UL Rating: | 300V RMS, 80°C and 300V, 105°C |
| UL AWM Style: | UL Style 1007 (300 V 80°C), UL Style 1569 (300 V 105°C) |
| CSA Rating: | 300V RMS, 105°C |
| CSA AWM Specification: | TRSR-64 |
| CSA Type: | TRSR-64 |
| Military Specification: | N/A |

Applicable Environmental and Other Programs

| | |
|--------------------------------|-----|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/96/EC (BFR): | Yes |

| | |
|---------------------------------------|-------------------------------|
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-10-01 |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Flammability, LS0H, Toxicity Testing

| | |
|--------------------|-----------|
| UL Flammability: | VW-1 |
| CSA Flammability: | FT1 |
| UL voltage rating: | 300 V RMS |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Part Number

Variants

| Item # | Color | Footnote |
|--------------|-------------|----------|
| 9928 010100 | Black | |
| 9928 0101000 | Black | P |
| 9928 013100 | Blue, Dark | |
| 9928 0131000 | Blue, Dark | P |
| 9928 001100 | Brown | |
| 9928 0011000 | Brown | P |
| 9928 0081000 | Gray | P |
| 9928 005100 | Green, Dark | |
| 9928 0051000 | Green, Dark | P |
| 9928 003100 | Orange | |
| 9928 0031000 | Orange | P |
| 9928 002100 | Red | |
| 9928 0021000 | Red | P |
| 9928 007100 | Violet | |
| 9928 009100 | White | |
| 9928 0091000 | White | P |
| 9928 004100 | Yellow | |
| 9928 0041000 | Yellow | P |

| | |
|-----------|---|
| Footnote: | P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'. |
|-----------|---|

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.