



NOTE

- MATERIAL
  - HEADER : LCP, GLASS FILLED, UL94V-0 HALOGEN FREE, COLOR OF NATURAL
  - CONTACT TERMINAL : COPPER-ALLOY, 0.3mm THICKNESS
- PLATING
  - CONTACT TERMINAL : TIN -PLATED
  - 0.84μm MINIMUM TIN PLATING
- PRODUCT SPECIFICATION : PS-104266-001
- PACKAGING SPECIFICATION : PK-104266-001
- COPLANALITY OF SOLDER TAILS (PEAK TEMP. : 260°C) BEFORE & AFTER REFLOW : 0.08 MAX.
- APPLICABLE SOLIDE WIRE RANGE :
  - (OUTSIDE WIRE INSULATION : 2.1mm DIAMETER MAX.)
  - SOLID WIRE : AWG #24~#18
  - STRAND WIRE : AWG #24~#20

RELEASED EC NO: KOR2016-0078 DRWN: SCHONG03 2016/02/20 CHKD: SHCHU 2016/02/20 APPR: YSK1M02 2016/03/03	DESCRIPTION QUALITY SYMBOLS $\nabla=0$ $\nabla=0$	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 6:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
			mm	INCH	DRAWN BY SCHONG03	DATE 2016/02/20	TITLE LITE TRAP CONN. BOTTOM ENTRY TYPE HEADER ASS'Y 1CKT		
		4 PLACES	± ---	± ---	CHECKED BY SHCHU	DATE 2016/02/20	<b>molex</b>		
		3 PLACES	± ---	± ---	APPROVED BY YSK1M02	DATE 2016/03/03			
2 PLACES	± 0.15	± ---	MATERIAL NO. 1042660110		DOCUMENT NO. SD-104266-001		SHEET NO. 1 OF 1		
1 PLACE	± 0.20	± ---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				
0 PLACE	± ---	± ---	ANGULAR ± 1 °						