

MAW SERIES

SPECIFICATIONS

G039-01-01 D

Items		Model	MAW-12R5	MAW-1201	MAW-1202	MAW-1203	MAW-1205
			-22	-22	-22	-22	-22
1	Rated Voltage (AC,DC)	-	250V				
2	Rated Current (AC,DC) (*1)	A	0.5	1	2	3	5
3	Test Voltage (terminals to case, 1min AC)	-	2500V(20mA) at 25°C , 70% RH				
4	Isolation Resistance (terminals to case, 500V DC)	-	100MΩ min at 25°C , 70% RH				
5	Leakage Current	125V,60Hz	0.5mA max				
		250V,60Hz	1mA max				
6	DC Resistance (both line)	Ω	5 max	1.5 max	0.6 max	0.3 max	0.2 max
7	Temperature Rise	-	30°C Max				
8	Operating Temperature	-	-25°C ~ +85°C				
9	Operating Humidity	-	30% ~ 95% RH (No Dewdrop)				
10	Storage Temperature	-	-40°C ~ +85°C				
11	Storage Humidity	-	10% ~ 95% RH (No Dewdrop)				
12	Vibration	-	10~55~10 Hz , Amplitude (Sweep for 1min) 1.5mm(88.3m/s ² max),X,Y,Z 2h each				
13	Safety Standards	-	Approved by UL1283 , CSA Std. C22. 2 No 8 , EN60939(VDE)				
14	Weight	g	95 typ	95 typ	95 typ	160 typ	160 typ

NOTE

*1 Value for $T_a \leq 55^\circ\text{C}$
 For $T_a > 55^\circ\text{C}$, derate
 according to the derating curve
 shown on the right.

