

Front adapters - FLKM S135/S400/SO121 - 2301736

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The FLKM S135/S400/SO adapter links a SIMATIC® S5 plug directly with the basic SIMATIC® S7 400 card.
Conversion: S5 card 6ES5 430-4UA14 to S7 card 6ES7-421-1BL01-0AA0



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	347.3 GRM
Custom tariff number	85369010
Country of origin	Germany

Technical data

General

Nominal voltage U_N	60 V DC
Max. permissible current	2 A (per path) 2 A (during supply via separate power supply)
Connection type, connector	SIEMENS S5-135 U pin strip
Mounting position	any
Standards/regulations	DIN EN 50178 IEC 62103

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Supported controller

Controller	SIEMENS S5-135 U
- suitable I/O card	6ES5 430-4UA14
Controller	SIEMENS S7-400

Front adapters - FLKM S135/S400/SO121 - 2301736

Technical data

Supported controller

- suitable I/O card	6ES7 421-1BL01-0AA0
---------------------	---------------------

Classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 6.0	27249205
eCl@ss 7.0	27249205
eCl@ss 8.0	27249205


ETIM

ETIM 2.0	EC000237
ETIM 3.0	EC000237
ETIM 4.0	EC000237
ETIM 5.0	EC002584


UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421

Drawings



Connection scheme: FLKM S135/S400/SO121



Connection scheme: FLKM S135/S400/SO121

