

Charging cable - EV-T2M4CC-DC125A-5,0M50ESBK00 - 1409060

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




Charging cable, Connector, Open cable end, IEC 62196-3 (type 2), Length: 5 m, Color of outer sheath: black, Charging mode: Mode 4

Product description

Open cable end



Key commercial data

Packing unit	1 PCE
GTIN	 4 046356 860581
Custom tariff number	85444290
Country of origin	GERMANY

Technical data

General data

Charging mode	Mode 4
Conductor length	5 m

Plug specifications

Standards/regulations	IEC 62196-3 (type 2)
Number of power contacts	3 (PE, DC+, DC-)
Rated voltage for power contacts	850 V DC
Rated current for power contacts	125 A
Number of signal contacts	2 (CP, PP)
Rated voltage for signal contacts	30 V AC
Rated current for signal contacts	2 A
Keying between PP and PE	1500 Ω

Charging cable - EV-T2M4CC-DC125A-5,0M50ESBK00 - 1409060

Technical data

Plug specifications

Insertion force	< 100 N
Withdrawal force	< 100 N
Insertion/withdrawal cycles	> 10000
Ambient temperature (operation)	-30 °C ... 50 °C
Degree of protection	IP44 (plugged in)
Degree of protection	IP24 (Not plugged in)

Cable specifications

Cable structure	2x 50 mm ² + 1x 25 mm ² + 3x 0.75 mm ²
External sheath, color	black
Type of conductor	Straight
External cable diameter	28 mm

Classifications

ETIM

ETIM 3.0	EC002061
ETIM 4.0	EC002061
ETIM 5.0	EC002839

UNSPSC

UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522
UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27279220
eCl@ss 7.0	27061801